





**Design for harsh industrial environments
 stable and reliable**

- ✓ Industrial Level 4
- ✓ IP40 protection
- ✓ CE,FCC certificated
- ✓ Anti-EMI

10M/100M Unmanaged Industrial PoE Switch

LV-GYFP204B

| Introduction | Image |
|--|---|
| <p>This unmanaged Ethernet PoE switch is specialized for harsh industrial environment. It is classified as power resource equipment, which can be used to power IEEE 802.3af/at compliant powered devices, eliminates the need of additional wiring.</p> <p>With simple operation, excellent quality and competitive price, it provides an economical solution for your industrial Ethernet network, which is also specially designed for the needs of multiplex broadband access with limited optical fibers.</p> |   |

| Features & Benefits |
|--|
| 4 IEEE 802.3af/at PoE compliance 10/100Base-T(X) ports and 2 100Base-FX port |
| Up to 30W at 48V DC power output on each PoE port |
| Super lightning protection, IP40 protection |
| Excellent heat elimination without cooling fan |
| Redundant dual DC power inputs |
| -40°C to +85°C operating temperature range |

| Switch Properties |
|------------------------------|
| MAC Table Size: 2K |
| Packet Buffer Size: 6KX64bit |



**Design for harsh industrial environments
stable and reliable**

- ✓ Industrial Level 4
- ✓ IP40 protection
- ✓ CE,FCC certificated
- ✓ Anti-EMI



| |
|---------------------------------------|
| Processing Type: Store and Forward |
| Exchange Properties: 148800pps (100M) |

| Physical Characteristics |
|---|
| Housing: Aluminum Alloy material with IP40 Protection |
| Dimension: 138mm(L) X 112mm(W) X 60mm(H) |
| Weight: 640g |
| Installation: Din-Rail mounting, Wall mounting |

| Interfaces |
|---|
| 4 RJ45 Ports Comply with IEEE802.3, IEEE802.3u, 10/100Base-T(X), IEEE802.3af/at PoE, 10/100Base-T(X) auto negotiation speed Full/Half duplex mode Auto MDI-MDI-X connection Up to 100M Cat-5 transmission distance |
| 2 Fiber Port Comply with IEEE802.3u, 100Base-FX Rate: 100Mbps Wavelength: 1310nm/1550nm Up to 2Km transmission distance with multi-mode Up to 20km,40km,60km,80km transmission distance with single-mode SC/ST/FC interfaces optional |



**Design for harsh industrial environments
stable and reliable**

- ✓ Industrial Level 4
- ✓ IP40 protection
- ✓ CE, FCC certificated
- ✓ Anti-EMI



| Power |
|--|
| Input Voltage: 48V DC(44-57VDC), Redundant dual inputs |
| Input Current: <0.5A @48VDC |
| Overload Current Protection: Present |
| Reverse Polarity Protection: Present |
| Redundant Protection: Present |
| Connection: 1 removable 6-pin terminal blocks |

| Environmental Limits |
|---|
| Operating Temperature: -40°C to +85°C |
| Storage Temperature: -40°C to +85°C |
| Ambient Relative Humidity: 5% to 95% (non-condensing) |

| Standard |
|--|
| Safety: UL 60950-1 |
| EMS: EN61000-4-2 (ESD), Level 3 EN61000-4-3 (RS), Level 3 EN61000-4-4 (EFT), Level 3 EN61000-4-5 (Surge), Level 3 EN61000-4-6 (CS), Level 3 EN61000-4-8, Level 3 |
| Shock: IEC 60068-2-27 |
| Free Fall: IEC 60068-2-32 |
| Vibration: IEC 60068-2-6 |
| EMI: FCC Part 15 Subpart B Class A, EN 55022 Class A |



**Design for harsh industrial environments
stable and reliable**

- ✓ Industrial Level 4
- ✓ IP40 protection
- ✓ CE,FCC certificated
- ✓ Anti-EMI

| |
|--------------------------|
| Industry: IEC61000-6-2 |
| Rail: EN50155, EN50121-4 |
| Traffic: NEMA TS-2 |

| |
|-----------------|
| Warranty |
| 5 years |

| Models Available | |
|-------------------------|---|
| Model No | Description |
| Dual Fiber | |
| LV-GYFP204B-MD | Multi-mode; 2Km; SC/ST/FC interfaces optional |
| LV-GYFP204B-SD | Single-mode; 20Km; SC/ST/FC interfaces optional |
| LV-GYFP204B-SD40 | Single-mode; 40Km; SC/ST/FC interfaces optional |
| LV-GYFP204B-SD60 | Single-mode; 60Km; SC/ST/FC interfaces optional |
| LV-GYFP204B-SD80 | Single-mode; 80Km; SC/ST/FC interfaces optional |
| Single Fiber | |
| LV-GYFP204B-MS | Multi-mode; 2Km; SC/ST/FC interfaces optional |
| LV-GYFP204B-SS | Single-mode; 20Km; SC/ST/FC interfaces optional |
| LV-GYFP204B-SS40 | Single-mode; 40Km; SC/ST/FC interfaces optional |
| LV-GYFP204B-SS60 | Single-mode; 60Km; SC/ST/FC interfaces optional |
| LV-GYFP204B-SS80 | Single-mode; 80Km; SC/ST/FC interfaces optional |